



7.5 : 10



Manufactured under one or more of the following U.S. patents: 3,681,618; 3,714,462; 3,789,143; 4,101,849; 4,697,767. Other patents pending.

REF DESIGNATIONS	
LAST	NOT USED
R35	
C2	
CR11	
OA3	
Q1	



NOTES:


1. UNLESS OTHERWISE SPECIFIED, A. ALL RESISTORS ARE EXPRESSED IN OHMS AND ARE 1/4W 5%. B. ALL CAPACITORS ARE EXPRESSED IN MICROFARADS. C. ALL LED'S ARE RED D. ALL OP AMPS ARE LM339

2. ALL LED CONNECTIONS MADE THROUGH J2

903 USED ON

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES AND/OR MILLIMETERS (mm)		APPROVAL	DATE
TOLERANCE ON INCHES		DRAWN	5/12/80
TOLERANCE ON MILLIMETERS (mm)		CHECKED	5/12/80
ANGLES		PROJ. ENG.	6/24/80
FRACTIONS		CH. ENG.	6/24/80
APPROVED FOR PRODUCTION TOOLING		RELEASED	6/24/80
DATE		SCALE	1 OF 1
REV		SIZE	NUMBER
01		C	61105-000
REV		01	

BRILLIANCE 40-107-37785



- NOTES:
- UNLESS OTHERWISE SPECIFIED:
 - A. ALL RESISTORS ARE EXPRESSED IN OHMS AND ARE 1/4W 5%.
 - B. ALL CAPACITORS ARE EXPRESSED IN MICROFARADS.
 - C. ALL DIODES ARE 1N4148.
 - D. ALL POLARIZED CAPS AND C3 ARE LOW ESR, LOW LEAKAGE, RADIAL CAPACITORS.
 - 2. SWITCH SHOWN IN "OUT" POSITION.
 - 3. * INDICATES HEATSINK ON DEVICE. (Q1 AND Q2)
 - 4. Δ SEE SELECTION PROCEDURE.

REF DESIGNATIONS	
LAST	NOT USED
R71	
C22	
OA6	
QA1	
CR15	
Q2	
Y3	
M1	
J1, S1	

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES AND/OR MILLIMETERS (mm)		APPROVAL	DATE
TOLERANCE ON INCHES		DRAWN	PV
TOLERANCE ON MILLIMETERS (mm)		CHECKED	GF6
ANGLES		PROJ. ENG.	JDL
FRACTIONS		CH. ENG.	LST
APPROVED FOR PRODUCTION TOOLING		RELEASED	DATE
APPROVED		DATE	SCALE
DATE		DATE	SCALE

AKG

ACOUSTICS

SCHEMATIC

COMPRESSOR /

LIMITER

903

USED ON

61104-000

01